

# GMI Holographics

## 2 MIL

This revolutionary new holographic imaged vinyl film is BRIGHTER than any traditional type product presently available. It should be applied to a smooth, flat surface for the best results. It can be used for POP displays, specialty stickers, and many other uses. **NOT RECOMMENDED FOR OUTDOOR USE.**

### ■ CONSTRUCTION

#### Face Film

2.0 mil rigid vinyl film (metallized)

#### Adhesive Release

Permanent, pressure-sensitive

#### Release Liner

96# Stay Flat

### ■ PHYSICAL PROPERTIES

#### Outdoor Durability

NOT RECOMMENDED FOR OUTDOOR USE.

#### Application Surface

Smooth, Flat Surface

#### Service Temperature Range

-50°F. to 275°F. - Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions.

#### Typical Film Caliper (w/adhesive)

2.7 - 3.0 mils

#### Product Variations

Available with a removable acrylic adhesive and can be top coated for improved ink adhesion.

#### Water Resistance

Excellent. Test piece aged 24 hrs after application to stainless steel panel before testing. Not affected when immersed in 70°F water for seven days.

#### Chemical Resistance

Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is always recommended. NOTE: Always pretest your specific substrate prior to actual application.

#### Humidity Resistance

Excellent.

#### Opacity

These films will completely hide black legend upon application.

#### Shelf Life

2 years when stored under conditions of 70°F. and 50 R. H.